Colour & Coatings

External Colour & Coating Ranges









Kingspan Colour & Coatings

Kingspan provides a large selection of external finishes and colours for its Standing Seam System, Insulated Roof & Wall Panels and Fabrications, Safety & Lighting Solutions, allowing building owners' and architects the ultimate flexibility in designing their building.



Kingspan Coatings

Kingspan offers the following range of coating systems suitable for external applications:



Kingspan coating systems offer many important advantages over those provided by any other coatings on the market:

Excellent corrosion resistance

Kingspan coatings are best in class for corrosion resistance. They use innovative metal alloy substrates, which provide maximum resistance to corrosion on scratches and on cut edges.

Advanced colour stability and UV resistance

Kingspan coloured coatings use state-of-the-art technology with improved UV resistance that provides better gloss retention and weather resistance.

Environmentally safe

Our coloured coating systems have been designed in accordance with Kingspan's sustainable development policy. They are phthalate-free, contain no heavy metals and are fully recyclable. Phthalate-free chemistry contributes to maintaining a safe and healthy environment.

Maintenance-free, saving time, trouble and cost

Kingspan coatings do not require any special maintenance regime and their performance will not deteriorate during their lifetime.


^{*}Please speak to your Kingspan Area Sales Manager about Minimum Order Quantities.

Extra reassurance where you need it



External Applications

Few materials are as colourful and durable as Kingspan XL Forté, a world class protective coating, that is available in a range of colours and provides a barrier against the elements when used in architectural roof and wall applications.



Technical Properties

Kingspan XL Forté				
Nominal thickness	200 µm	Condensation resistance (QCT test)	1500 hours	
Gloss (Gardner 60 °C)	15-45 GU	Temperature resistance	Maximum 75 °C	
Appearance	Embossed leathergrain	UV resistance (QUV-A test 2000 hours):		
Adhesion of the coating (T-bend)	≤ 0,5 T	Colour change	ΔE ≤ 2 ≥ 80% RUV4	
Scratch resistance (Clemen)	≥ 4,5 kg	Gloss retention		
Abrasion resistance (Taber)	≤ 30 mg	Category (EN 10169-1/2)		
Impact resistance	18 J	Resistance to acids and bases	Good to very good	
Surface pencil hardness	4 – 6B	Resistance to solvents:		
Resistance to cracking on bending (T-bend)	≤ 1,5 T	Aliphatics and alcohols Ketones	Very good Low	
Corrosion resistance:		Aromatics	Good to very good	
Salt spray test	1000 hours	Resistance to mineral oils	Very good	
Category RC5		Fire classification (EN 13501-1)	Cs2,d0	


Coating Warranty Periods

	Inland Roof	Inland Wall	Coastal Roof**	Coastal Wall**
Kingspan XL Forté	40 years	40 years	30 years	30 years
Kingspan XL Forté*	30 years	40 years	25 years	30 years

^{*} Please note the reduction in the roof warranty that is applicable to specific colours within this range.

For more information on colours please refer to the Kingspan Insulated Roof & Wall Panels Colour Range chart.

Kingspan Spectrum is a proven coating that delivers aesthetic brilliance and guaranteed performance in a variety of applications. Kingspan Spectrum provides a robust barrier against the elements when used on façades or in architectural roof and wall systems.



Coating Warranty Periods


	Inland Roof	Inland Wall	Coastal Roof*	Coastal Wall*
Kingspan Spectrum Solid	30 years	30 years	25 years	25 years
Kingspan Spectrum Metallic	30 years	30 years	25 years	25 years

^{*} Coastal refers to buildings within 1km of the coast.

For more information on colours please refer to the Kingspan Insulated Roof & Wall Panels Colour Range chart.

^{**} Coastal refers to buildings within 1 km of the coast.

Kingspan Altaris is the finest-looking exterior coating in our range, featuring colour purity, strength, resistance and stability. It provides unparalleled protection against environmental weathering and is perfectly suited for high-end applications. It is available in a wide range of highly polished and two-tone colours.




Coating Warranty Periods

	Inland Roof	Inland Wall	Coastal Roof*	Coastal Wall*
Kingspan Altaris 2L	N/A	30 years	N/A	n.v.t
Kingspan Altaris 3L	N/A	40 years	N/A	20 years
Kingspan Altaris 4L	N/A	40 years	N/A	20 years

^{*} Coastal refers to buildings within 1km of the coast.

For more information on colours please refer to the Kingspan Insulated Roof & Wall Panels Colour Range chart.


Kingspan Destral is a versatile organic polyester coating proven to satisfy the universal requirements for solidity, flexibility, durability, and cost-effectiveness.



Technical Properties

Kingspan Destral			
Nominal thickness	40 µm	Condensation resistance (QCT test)	1500 hours
Gloss (Gardner 60 °C)	< 5 GU	Temperature resistance	Maximum 90 °C
Appearance	Grained	UV resistance (QUV-A test 2000 hours):	
Adhesion of the coating (T-bend)	≤ 1 T	Colour change	ΔE ≤ 3
Impact resistance	18 J	Gloss retention	≥ 60% RUV3
Surface pencil hardness	HB to H	Category (EN 10169-1/2)	
Resistance to cracking on bending	≤ 2 T	Resistance to acids and bases	Good
(T-bend)	S Z I	Resistance to solvents:	
Corrosion resistance:		Aliphatics and alcohols	Very good
Salt spray test	500 hours	Ketones	Low
Category	RC4	Aromatics	Good to very good






^{*}Please speak to your Kingspan Area Sales Manager about Minimum Order Quantities.






^{*}Please speak to your Kingspan Area Sales Manager about Minimum Order Quantities.





^{*}Please speak to your Kingspan Area Sales Manager about Minimum Order Quantities.





^{*}Please speak to your Kingspan Area Sales Manager about Minimum Order Quantities.






^{*}Please speak to your Kingspan Area Sales Manager about Minimum Order Quantities.



Kingspan's range of colourful translucent multi-wall polycarbonate for roof and wall applications, with UV protected layers that allow high levels of natural light to pass through.



^{*}Please speak to your Kingspan Area Sales Manager about Minimum Order Quantities.

20

Kingspan XL Forté

A range of world class protective PVC coatings with a leathergrain effect that is available in inspiring colours and provides a barrier against the elements.



For stock levels, minimum order quantities and/or lead times, contact the Kingspan Quotations Department.

The printed colours are as accurate as possible but are for guidance purposes only. British Standard (BS) or RAL reference numbers represent the nearest colours and are not exact matches to our Kingspan coatings. Please ensure that you request a swatch sample from the Kingspan Marketing Department to view accurate colour and texture prior to specification.

^{*} Please note the warranty periods for these colours are as for XL Forté* – see warranty table on page 25.

Kingspan Spectrum

A range of proven smooth polyurethane coatings that delivers aesthetic brilliance and guaranteed performance in a variety of applications.



Kingspan Spectrum Metallic







Silver RAL 9006



Obsidian RAL 9007



Graphite RAL 9023



Greyrock KC 100



Topaz KC 200



Opal KC 400

For stock levels, minimum order quantities and/or lead times, contact the Kingspan Quotations Department.

The printed colours are as accurate as possible but are for guidance purposes only. British Standard (BS) or RAL reference numbers represent the nearest colours and are not exact matches to our Kingspan coatings. Please ensure that you request a swatch sample from the Kingspan Marketing Department to view accurate colour and texture prior to specification.

Kingspan Altaris

Technically advanced PVDF multi-layer (up to 4 layers of paint) coatings featuring colour purity, strength, resistance and stability. This range provides unparalleled protection against environmental weathering and is available with a high gloss finish.



For stock levels, minimum order quantities and/or lead times, contact the Kingspan Quotations Department.

The printed colours are as accurate as possible but are for guidance purposes only. British Standard (BS) or RAL reference numbers represent the nearest colours and are not exact matches to our Kingspan coatings. Please ensure that you request a swatch sample from the Kingspan Marketing Department to view accurate colour and texture prior to specification.

Kingspan Textured

A range of elastomeric acrylic rendered effect coatings that provides a protective weathering membrane which is extremely durable, fade and mildew resistant.



Kingspan Destral

Matt polyester organic coatings that are ideal for the Kingspan Roof Tile System.





Terracotta RAL 8004

Jet Black RAL 9005

For stock levels, minimum order quantities and/or lead times, contact the Kingspan Quotations Department.

The printed colours are as accurate as possible but are for guidance purposes only. British Standard (BS) or RAL reference numbers represent the nearest colours and are not exact matches to our Kingspan coatings. Please ensure that you request a swatch sample from the Kingspan Marketing Department to view accurate colour and texture prior to specification.

24

Kingspan Day-Lite

A range of colourful translucent multi-wall polycarbonate for roof and wall applications, with UV protected layers that allow high levels of natural light to pass through.



Infra-Red (IR) Absorbing Lights

These two colours absorb greater levels of infra-red light which reduces solar gain. This can allow for greater control of ambient temperature within the building providing a possible reduction in HVAC usage.

Membranes

High performance polyvinyl chloride (PVC) and thermoplastic elastomer (TPE) single-ply membranes specifically designed for roof applications and fabrications.



Armourplan Light Grey PVC RAL 7047



Armourplan Mid Grey PVC RAL 7046



Sika-Trocal Grey PVC RAL 7047



Sika-Trocal Slate PVC **RAL 7015**

Kingspan Guarantees

In recognition of the many different demands that are placed on construction professionals today, Kingspan Insulated Panels offers comprehensive warranties on not just one aspect of its products, but all of the key performance areas.

Kingspan Warranties provide market-leading protection that covers the coating, durability, structural, fire and thermal performance of a product in a single, unique package.

Kingspan Insulated Panels sources its colour coated metal from several world class coatings suppliers and the Warranty includes a coatings protection against corrosion, chemical attack, ultra-violet radiation, humidity and abrasion for up to 40 years (in nominated geographic zones), so the building owner can be sure that the building will continue to look good year on year. The thermal efficiency and structural performance of the panels are warranted for periods of up to 40 years.

Please note that the installation of Kingspan Energy's Roof Mounted PV System will not affect the Kingspan Warranty and that Kingspan Insulated Panels will stand by the full warranty presented below.

The below table refers to warranty periods for the United Kingdom:

	Inland Roof	Inland Wall	Coastal Roof**	Coastal Wall**
Kingspan XL Forté	40 years	40 years	30 years	30 years
Kingspan XL Forté*	30 years	40 years	25 years	30 years
Kingspan Spectrum Solid	30 years	30 years	25 years	25 years
Kingspan Spectrum Metallic	30 years	30 years	25 years	25 years
Kingspan Altaris (ALL) 2L	N/A	30 years	N/A	N/A
Kingspan Altaris (ALL) 3L	N/A	40 years	N/A	20 years
Kingspan Altaris (ALL) 4L	N/A	40 years	N/A	20 years
Kingspan Textured	N/A	25 years***	N/A	25 years***
Kingspan Destral	15 years	N/A	10 years	N/A
Kingspan Day-Lite [†]	25 years	25 years	25 years	25 years
Membranes	A 15 year warranty is available as standard. For warranties in excess of 15 years, please contact Kingspan Technical Services.			

For warranty periods for Ireland, please contact our Technical Services Department on +353 (0) 42 96 98529.

- * Please note the reduction in the roof warranty that is applicable to specific colours within this range.
- ** Coastal refers to buildings within 1 km of the coast.
- $\ensuremath{^{***}}$ Coating will require repainting every ten years in order to comply with warranty.
- † Project specific and can vary. Please contact us for further information.

Sustainability

Commitment to Sustainability

With a number of significant advancements in the European climate change and energy performance agenda over the past 12 months, it has never been more important for businesses to recognise and take responsibility for their impact on the environment. Kingspan Insulated Panels has been leading the way with its dedication to sustainable business practice.

Our UK manufacturing operations have now achieved Net-Zerc Energy status and are certified 'Very Good' under BES 6001: Responsible Sourcing of Construction Products. Our panel products are manufactured with a HCFC, CFC more in our Sustainability report available online.

Kingspan has developed third party verified EN 15804: 2012 environmental product declarations (EPD's) for QuadCore™ nsulated panel systems. EPD's provide technical and quantified environmental information across a product's lifespan.

Kingspan Insulated Panels Environmental Product Declarations (EPDs) are available on our website.





UK

Kingspan Limited

Greenfield Business Park No.2 Greenfield, Holywell Flintshire, CH8 7GJ T: +44 (0) 1352 716100 F: +44 (0) 1352 710161 www.kingspanpanels.co.uk

Ireland

Kingspan Limited

Carrickmacross Road Kingscourt, Co Cavan Ireland Tel: +353 (0) 42 96 98500

Fax: +44 (0) 42 96 98572 info.ire@kingspanpanels.com www.kingspanpanels.ie

For the product offering in other markets please contact your local sales representative or visit www.kingspanpanels.com

Care has been taken to ensure that the contents of this publication are accurate, but Kingspan Limited and its subsidiary companies do not accept responsibility for errors or for information that is found to be misleading. Suggestions for, or description of, the end use or application of products or methods of working are for information only and Kingspan Limited and its subsidiaries accept no liability in respect thereof.

